

MADE IN CANADA WWW.BULKSEALER.ON.CA

# SAFETY DATA SHEET - JET BLACK ASPHALT EMULSION

Issuing Date January 20 2023 Revision Date February 02 2024 Revision Number 1

# 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING

**GHS Product Identifier** 

Product Name: Jet Black Asphalt Emulsion

Other Means of Identification

Product Code(s): Jet Black AE

Synonyms None

Recommended Use of the Chemical and Restrictions on Use

Recommended Use: No Information Available
Uses Advised Against: No Information Available

# Supplier's Details

### Supplier Address

PDQ Bulk Sealer 120 Chatham St Hamilton, Ontario, Canada www.bulksealer.on.ca 1-905-525-2476

### **Emergency Telephone Number**

Emergency Telephone Number Chemtrec 1-800-424-9300

# 2. HAZARDS IDENTIFICATION

### Classification

This chemical is not considered hazardous according to the OSHA Hazard Communication Standard 2012 (29 CFR 1910.1200).

# **GHS Label Elements, Including Precautionary Statements**

### **Emergency Overview**

Signal Word Warning

Harmful if swallowedMay cause skin irritation

●May cause skin irritatio

Appearance:BlackPhysical State:LiquidOdor:Asphaltic





**Precautionary Statements** 

**Prevention** Inhalation: May cause irritation of respiratory tract.

**Eye Contact:** Contact with eyes may cause irritation.

**Skin Contact:** May cause irritation.

Ingestion: Ingestion may cause stomach discomfort.

General Advice •None

Storage • Keep container tightly closed

Disposal •Dispose of material/containers in accordance with the appropriate state, regional, or local

regulations.

### Hazard Not Otherwise Classified (HNOC)

Not applicable

#### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS Number	Weight %	Trade Secret
Limestone	1317-65-3	20-40	*
Asphalt	8052-42-4	20-40	*
Kaolin	1332-58-7	<10	*
Bentonite	1302-78-9	<10	*

<sup>\*</sup>The exact percentage of composition has been withheld as a trade secret.

### 4. FIRST AID MEASURES

Description of Necessary First-Aid Measures

Eye Contact Rinse thoroughly with plenty of water, also under the eyelids. If symptoms persist, call a

physician.

Skin Contact Wash off immediately with soap and plenty of water. In the case of skin irritation or allergic

reactions, see a physician.

**Inhalation** Move to fresh air. If symptoms persist, call a physician.

**Ingestion** Drink plenty of water. Do NOT induce vomiting. Never give anything by mouth to an

unconscious person. Consult a physician if necessary.

Most Important Symptoms/Effects, Acute and Delayed

Most Important Symptoms/Effects No information available

Indication of Immediate Medical Attention and Special Treatment Needed, If Necessary

Notes to Physician Treat Symptomatically. May cause sensitization by skin contact.

# 5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Carbon Dioxide (CO<sub>2</sub>). Dry Chemical. Foam. Water Fog.

**Unsuitable Extinguishing Media** CAUTION: Use of water spray when fighting fire may be inefficient.

# Specific Hazards Arising from the Chemical

No information available

**Explosion Data** 

Sensitivity to Mechanical Impact None Sensitivity to Static Discharge None

# **Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure- demand MSHA/NIOSH (approved or equivalent) and full protective gear.





#### 6. ACCIDENTAL RELEASE MEASURES

### Personal Precautions, Protective Equipment, and Emergency Procedures

Personal Precautions: Ensure adequate ventilation. Avoid contact with skin, eyes and clothing. Use personal

protective equipment.

**Environmental Precautions** 

Environmental Precautions: See Section 12 for additional Ecological Information

### Methods and Materials for Containment and Cleaning Up

**Methods for Containment:** Prevent further leakage or spillage if safe to do so.

Methods for Cleaning Up: Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled

containers. Clean contaminated surface thoroughly.

### 7. HANDLING AND STORAGE

# **Precautions for Safe Handling**

Handling: Handle in accordance with good industrial hygiene and safety practice. Avoid contact with

skin, eyes, and clothing. Wear personal protective equipment. Avoid breathing vapors or mists. Do not eat, drink, or smoke when using this product. Wash thoroughly after

handling.

### Conditions for Safe Storage, Including Any Incompatibilities

Storage:Keep container tightly closedIncompatible Products:Strong oxidizing agents. Acids.

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

# **Control Parameters**

#### **Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Limestone 1317-65-3	-	TWA: 15 mg/m³ TWA: 5 mg/m³ (vacated) TWA: 15 mg/m³ (vacated) TWA: 5 mg/m³	TWA: 5 mg/m³ respirable dust TWA 10 mg/m³ total dust
Asphalt 8052-42-4	TWA: 0.5 mg/m³ benzene soluble aerosol fume, inhalable fraction	-	Ceiling: 5 mg/m³ fume 15 min.
Kaolin 1332-58-7	-	TWA: 15 mg/m³ total dust TWA: 5 mg/m³ respirable fraction (vacated) TWA: 10 mg/m³ total dust (vacated) TWA 5 mg/m³ respirable fraction	TWA: 15 mg/m³ total dust TWA: 5 mg/m³ respirable dust
Bentonite 1302-78-9	TWA 1 mg/m³ respirable fraction	-	-

#### **Appropriate Engineering Controls**

Engineering Measures: Showers

Eyewash Stations Ventilation Systems

# Individual Protection Measures, such as Personal Protective Equipment

Eye/Face Protection: If splashes are likely to occur, wear: Safety glasses with side shields.

Skin and Body Protection: Impervious gloves.

Respiratory Protection: No protective equipment is needed under normal use conditions. If exposure limits are

exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should

be worn

Hygiene Measures: Handle in accordance with good industrial hygiene and safety practice.





#### 9. PHYSICAL AND CHEMICAL PROPERTIES

### Information on Basic Physical and Chemical Properties

Physical State: Liquid Appearance: Black

Odor: Asphaltic Odor Threshold: No Information Available

<u>Property</u> <u>Values</u> <u>Remarks/Method</u>

 pH
 No data available
 None known

 Melting Point/Range
 No data available
 None known

Boiling Point/Boiling Range 100° C None known

Flash PointNo data availableNone knownEvaporation RateNo data availableNone knownFlammability (solid, gas)No data availableNone known

Flammability Limits in Air
Upper flammability limit
Lower flammability limit
No data available
No data available

Vapor Pressure No data available None known Vapor Density No data available None known Specific Density 1.24 @ 77 F None known Water Solubility Easily dispersible None known Solubility in other solvents No data available None known Partition coefficient: n-octanol/water No data available None known **Autoignition Temperature** No data available None known **Decomposition Temperature** No data available None known Viscosity No data available None known

Flammable Properties

Explosive Properties

Oxidizing Properties

No data available
No data available

Other Information

VOC Content Less than 15 g/l

# 10. STABILITY AND REACTIVITY

Reactivity: No data available

Chemical Stability: Stable under recommended storage conditions.

Possibility of Hazardous Reactions: None under normal processing.

**Hazardous Polymerization:** Hazardous polymerization does not occur.

Conditions to Avoid: None known

**Incompatible Materials:** Strong oxidizing agents. Acids.

Hazardous Decomposition Products: Carbon Monoxide (CO), Carbon Dioxide (CO²), Hydrogen Sulfide, Nitrogen Dioxide

# 11. TOXICOLOGICAL INFORMATION

# Information on Likely Routes of Exposure

**Product Information** 

Inhalation: May cause irritation of respiratory tract.

Eye Contact: Contact with eyes may cause irritation.

**Skin Contact:** May cause irritation.

**Ingestion:** Ingestion may cause stomach discomfort.

Chemical Name	LD50 Oral	LD50 Dermal	LD50 Inhalation
Asphalt	5000 mg/kg (Rat)	>2000 mg/kg (Rabbit)	-
Bentonite	>5000 mg/kg (Rat)	-	-

# Symptoms Related to the Physical, Chemical, and Toxicological Characteristics

Symptoms: No information available.





# Delayed and Immediate Effects and also Chronic Effects from Short and Long Term Exposure

Sensitization: No information available. Mutagenic Effects: No information available.

Carcinogenicity: The table below indicates whether each agency has listed any ingredient as a carcinogen.

The IARC, NTP, and OSHA do not list asphalt as a carcinogen. In general, the oxidation of polycyclic aromatic hydrocarbons destroys their carcinogenic potential. Petroleum asphalt, shale oil asphalts, and coal tars show distinct variation in their relative carcinogenicity for

experimental animals.

Chemical Name	ACGIH	IARC	NTP	OSHA
Asphalt	A3	Group 2B	Reasonably Anticipated	Χ

ACGIH: (American Conference of Governmental Industrial Hygienists)

A3 – Animal Carcinogen

IRAC: (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

NTP: (National Toxicity Program)

Reasonably Anticipated – Reasonably Anticipated to be a Human Carcinogen OSHA: (Occupational Safety & Health Administration)

X – Present

Reproductive Toxicity: No information available. STOT - Single Exposure: No information available. No information available. STOT – Repeated Exposure: Aspiration Hazard: No information available.

Numerical Measures of Toxicity - Product

The following values are calculated based on Chapter 3.1 of the GHS document

LD50 Oral: 12542 mg/kg; Acute toxicity estimate LD50 Dermal 6181 mg/kg, Acute toxicity estimate

# 12. ECOLOGICAL INFORMATION

#### **Ecotoxicity**

The environmental impact of this product has not been fully investigated.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Bentonite 1302-78-9		LC50 96 h: 8.0-19.0 g/L (Salmo gairdneri) LC50 96 h: = 19000 mg/L static (Oncorhynchus		
		mykiss)		

Persistence and Degradability: No information available

Bioaccumulation

	<del>-</del>
Chemical Name	Log Pow
Asphalt	6 006

Other Adverse Effects: No information available.

### 13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods: This material, as supplied, is not a hazardous waste according to Federal regulations (40

CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional,

or local regulations for additional requirements.

Contaminated Packaging: Do not re-use empty containers.

# 14. TRANSPORTATION INFORMATION

DOT: Not regulated





# Delayed and Immediate Effects and also Chronic Effects from Short and Long Term Exposure

Sensitization: No information available. Mutagenic Effects: No information available.

Carcinogenicity: The table below indicates whether each agency has listed any ingredient as a carcinogen.

The IARC, NTP, and OSHA do not list asphalt as a carcinogen. In general, the oxidation of polycyclic aromatic hydrocarbons destroys their carcinogenic potential. Petroleum asphalt, shale oil asphalts, and coal tars show distinct variation in their relative carcinogenicity for

experimental animals.

Chemical Name	ACGIH	IARC	NTP	OSHA
Asphalt	A3	Group 2B	Reasonably Anticipated	Χ

ACGIH: (American Conference of Governmental Industrial Hygienists)

A3 – Animal Carcinogen

IRAC: (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

NTP: (National Toxicity Program)

Reasonably Anticipated – Reasonably Anticipated to be a Human Carcinogen OSHA: (Occupational Safety & Health Administration)

X – Present

Reproductive Toxicity: No information available. STOT - Single Exposure: No information available. No information available. STOT – Repeated Exposure: Aspiration Hazard: No information available.

Numerical Measures of Toxicity - Product

The following values are calculated based on Chapter 3.1 of the GHS document

LD50 Oral: 12542 mg/kg; Acute toxicity estimate LD50 Dermal 6181 mg/kg, Acute toxicity estimate

# 12. ECOLOGICAL INFORMATION

#### **Ecotoxicity**

The environmental impact of this product has not been fully investigated.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Bentonite 1302-78-9		LC50 96 h: 8.0-19.0 g/L (Salmo gairdneri) LC50 96 h: = 19000 mg/L static (Oncorhynchus		
		mykiss)		

Persistence and Degradability: No information available

Bioaccumulation

	<del>-</del>
Chemical Name	Log Pow
Asphalt	6 006

Other Adverse Effects: No information available.

### 13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods: This material, as supplied, is not a hazardous waste according to Federal regulations (40

CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional,

or local regulations for additional requirements.

Contaminated Packaging: Do not re-use empty containers.

# 14. TRANSPORTATION INFORMATION

DOT: Not regulated





#### 15. REGULATORY INFORMATION

#### International Inventories

TSCA - Complies
DSL/NDSL - Complies

#### <u>Legend</u>

TSCA – United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL – Canadian Domestic Substances List/Non-Domestic Substances List

#### **U.S. Federal Regulations**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	CAS Number	Weight %	SARA 313 – Threshold Values %
Asphalt	8052-42-4	20-40	0.1

#### SARA 311/312 Hazard Categories

Acute Health Hazard	No
Chronic Health Hazard	No
Fire Hazard	No
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

### Clean Water Act

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

#### **CERCLA**

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific requirements at the local, regional, or state level pertaining to releases of this material.

#### U.S. State Regulations

California Proposition 65: This product does not contain any Proposition 65 chemicals.

# U.S. State Right-To-Know Regulations

"X" designates that the ingredients are listed on the state right to know list.

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Illinois	Rhode Island
Limestone	X	X	X		X
Asphalt	X	X	X		X
Kaolin	X	X	X		X
Carbon Black	Х	X	Х	X	Χ

# U.S. EPA Label Information

EPA Pesticide Registration Number: Not applicable

16	OTHER	INFORMATION
10.	CITER	INFURINATION

NFPA Health Hazard: 1 Flammability: 0 Instability: 0 Physical and Chemical Hazards-HMIS Health Hazard: 1 Flammability: 0 Physical Hazard: 0 Personal Protection: X

# General Disclaimer

The information provided on this SDS is correct to the best of our knowledge, information, and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.



